

**REVISIONS** ZONE REV DESCRIPTION DATE APPROVED A INITIAL RELEASE 7/9/02 DG ADDED FLAGNOTE 6 3/14/03

\_6" MAX. TYP 6 FIXED OBJECT (SEE ABOVE FOR PROPER POSITIONING) 2100 1400 1400 2100 1400 1400 6" MIN. TYP

THIS DRAWING IS AN EXAMPLE OF A TYPICAL ARRAY PLAN AND SHOULD IN NO WAY OVERRIDE WHAT IS SPECIFIED BY YOUR LOCAL OR STATE TRAFFIC ENGINEER. CONTACT YOUR LOCAL OR STATE TRAFFIC ENGINEER FOR SPECIFIC SITE RECOMMENDATIONS FOR EACH SITUATION.

6. FOR FIXED OBJECT WIDTHS GREATER THAN 18" INCREASE SPACING OF DOUBLE WIDE BARRELS UP TO 12" APART.

- 5. PLACE THE TYPE P MARKER PANEL SO THAT THE BOTTOM OF THE PANEL IS AT THE BOTTOM OF THE MODULE.
- 4. MASS OF SAND AND OUTLINE OF EACH MODULE SHALL BE PAINTED ON THE SURFACE OF EACH MODULE LOCATION.
- 3. BIDIRECTIONAL CRASH CUSHION ARRAYS MAY BE ANGLED TOWARD APPROACHING TRAFFIC. AMOUNT OF ANGLE NOT TO EXCEED 10°.
- 2. EACH MODULE IS TO CONTAIN AMOUNT OF SAND INDICATED. ALL SAND MASSES ARE NOMINAL.
- (XXX) INDICATES MODULE LOCATION AND MASS OF SAND IN POUNDS (LBS) FOR EACH MODULE. MODULE SPACING IS BASED ON THE GREATER DIAMETER OF THE MODULE.

NOTES: UNLESS OTHERWISE SPECIFIED.

4−24"−►

UNLESS OTHERWISE SPECIFIED: ALL DIMENSIONS ARE IN INCHES.		TrafFix Devices Inc.				Sar (94) FAX	220 Calle Pintoresco San Clemente, CA 92672 (949) 361-5663 FAX (949) 361-9205 www.traffixdevices.com			
DDAHAL DV	LDATE.		25	BARF	REL, H (4	AR 10	RAY KPI	, '		
DRAWN BY: J. HARDMAN	DATE: 7/8/02	0175		, , , ,	, , ,					
CHECKED BY:	DATE:	SIZE			DWG NO.	B	A25		REV	
APPROVED BY: D. GERTZ	DATE: 7/8/02	SCALE	NONE				SHEET	1 OF	1	

