

**TraFFix
Devices Inc.**



ENVIRO-CONE®

Engineered Products for Safer Highways



Made in the USA means a reliable, consistent and sustainable source of supply for distributors and users throughout North America.

Recyclable

- The Enviro-Cone® is 80% recycled by weight and can be recycled again. No more landfills loaded with toxic PVC cones. Enviro-Cone also qualifies for Green Points due to its high recycled content.
- If ever a stem gets destroyed, simply reorder the stem and reuse the base. No need to buy the entire cone.

Cold & Hot Weather Performance

- Manufactured from low density polyethylene, the Enviro-Cone provides superior cold weather performance. No cracking or breaking down to -40°F.
- No more soft and droopy cones in hot weather. The Enviro-Cone stands tall and vertical in road temperatures exceeding 180°F.

Stock # 16028-HIWB-7
28" Tall, 7 lb. with (6" & 4") reflective collars. MUTCD Compliant



Gription

- The Easy Grip Groove provides excellent "gription" for quick deployment and retrieval. Also makes tying off caution tape to cone quick and easy.

Visibility

- Quality 3M reflective collars assure superior performance in low light and nighttime conditions.

Durability

- Enviro-Cone provides long term durability. Color retention is excellent through the use of ultraviolet stabilizers and low density polyethylene (LDPE) increases the life of the product.

Stability

- With nearly 80% of the weight in the base, the Enviro-Cone is more stable than traditional 7 or 10 lb. PVC cones.

Complete Enviro-Cone Family

- Available in 18, 28 and 36 inches. Cone weights of 3, 7, 10 or 12 lbs. All sizes available in lime and white.



18", 3# 16018-HIWB-3 28", 7# 16026-HIWB-7 28", 10# 16028-HIWB-10 28", 12# 16028-HIWB-12 36", 10# 16036-HIWB-10 36", 12# 16036-HIWB-12 36", 12# 16036-L-HIWB-12 36", 10# 16036-L-HIWB-10 28", 12# 16028-L-HIWB-12 28", 10# 16028-L-HIWB-10 28", 7# 16028-L-HIWB-7 18", 3# 16018-L-HIWB-3

PRODUCT BULLETIN

ENVIRO-CONE®



Tire impact



No ripped or torn PVC,
simply reshape



Drop base over
stem and reuse


Enviro-Cone® Specification

Orange traffic cone shall be 28" in height and have a total weight of 7 lbs. +/- .25 lbs. Stem of the cone shall be molded from LDPE to provide superior cold/hot weather performance, excellent 100% UV resistance/color retention, and superior impact performance. Base of the cone shall be molded from recycled rubber and make up approximately 80% of the total weight. Dimensions of the base are to be 15 3/4"x15 3/4". Cone base shall be removable so that the stem can be replaced. Base will lock onto the stem with molded-in locking lugs on the stem. The stem of the cone shall have recesses for reflective collars and a groove near the top of the cone for easy gription. Tipping angle of the cone shall be no less than 76° from vertical . The stem and base of the traffic cone shall be made in the USA.

Stability Improvement


Tipping Point Comparison

PVC Cones vs. Enviro-Cone




7 lb. PVC

60% of weight in base
40% of weight in stem



10 lb. PVC



7 lb. Enviro-Cone

80% of weight in base
20% of weight in stem

**TraFFix
Devices Inc.**



Engineered Products for Safer Highways

160 Avenida La Pata, San Clemente, CA 92673
(949) 361-5663 FAX (949) 361-9205

www.traffixdevices.com

Distributed by: